

SPC	Characteristics	Norm	Unit	Result	
<div style="text-align: center;"> <p>CLICK SPC</p> </div> <div style="text-align: center; margin-top: 20px;"> </div> <div style="text-align: center; margin-top: 20px;"> <p>www.prodinex.com</p> </div> <div style="display: flex; justify-content: space-around; margin-top: 20px;"> <div style="text-align: center;"> </div> <div style="text-align: center;"> </div> </div> <div style="display: flex; justify-content: space-around; margin-top: 20px;"> <div style="text-align: center;"> </div> <div style="text-align: center;"> </div> <div style="text-align: center;"> </div> </div>	Kind	EN ISO 10582	G - serie	heterogeneous PVC	
	Thickness total	EN ISO 24346 EN 428		mm	6,5 (4,5 SPC+2,0 IXPE)
	Waerkayer thickness	EN ISO 23340		mm	0,55
	Width			mm	225
	Length			mm	1230
	Weight	EN ISO 23997 EN 430		g/m2	± 9300
	Micro bevelled		4V		4-sides
	Coating wearlayer				PUR
	Utilization class	EN 685		residential	23
				commercial	33
				industrial	42
	Dimensional stability	EN 23999		%	≤ 0,1
	Curling	EN 23999		mm	≤ 0,1
	Residual indentation	EN ISO 24343-1		mm	< 0,25
	Castor chair effect	EN 425			No, type W
	Colour fastness to light	EN ISO 105-B02		on Wooolskala	≥ 6
	CE certificate	EN 14041	CE	2004/AC:2006	yes
	Reaction to fire and smoke development	EN 13501-1		class	Bfl-S1
	Formaldehyde emission	EN 717-1		class	E 0
	PCP value	EN 14041		ppm	0
	Slip resistance (dry)	EN 13893		class	DS
	Anti-slip	DIN 51130		category	R 10
	Chemical resistance	EN ISO 26987 EN 423		class	1
	Staining resistance	EN ISO 26987 EN 423		class	2
	Abrasion resistance	EN 660-2		class	T
	Electrical behaviour	EN 1815		kV	< 2
	Thermal conductivity	EN 12667		m2K/W	0,075
	Floor heating suitability	output temp.		good	max 28 degrees
Impact noise reduction	EN ISO 717-2 / 140-8		ΔLw	21 dB	
walking noise reduction				good	
Waterproof suitable for moistured rooms				yes	
Stair suitability				yes	
Guarantee	residential		year	25	
	commercial industrial		year	10	